

# Kid Sized Olson Mask Instructions

- Print the first two pages back to back. The “do not cut” text should appear on the back of two pattern pieces. Hold up the paper to a light - does the 1” test box line up through the paper?
- Cut out the 3 double-sided pattern pieces.
- You will have 5 pieces to cut... Inside A, B, and C & Outside A and B. Trace each piece one time on the wrong side of your fabric, flipping the pattern pieces as necessary.
- Straight stitch Inside B to Inside C, (along the similar length straight edge) leaving a 3/4” gap at the top. Press seam open.
- Serge or straight stitch Inside A to Inside B/C along the curve. Likewise with Outside A to Outside B.
- Press Inside panel and Outside panels open along their curves.
- Serge or straight stitch Inside panel to Outside panel along the long top and bottom edges, leaving the sides open.
- Flip and press flat.
- Press unfinished sides of the mask 1/4” (towards mask center) then again 1/2”, now hiding the unfinished seam. Sandwich your elastic or thread your ribbon through while pinning.
- Stitch the mask sides closed.
- Mark a line along the nose bridge 3/4” down from the top edge, about 1.5” on either side of the center seam. Stitch along this line. You have now made a nose band channel, that lines up with the finished hole (between Inside B and C.) Use this to place a 3” piece of pipe cleaner for proper mask fit. It is removeable for washing.
- Wash and dry in HIGH HEAT, without the pipe cleaner in place. Change out masks every couple of hours.